



ISO8528

CE

• u\_i\_j ; ~ Wž%: Unž) \$<nj Y\* \$<nž; : %ž\$

	rVA	kW	
120/240	27	27	225/113
110/220	27	27	245/123
115/230	27	27	235/117
120/240	27	27	225/113

• Standart Özellikler

GUV]hiYg]gYfXYžmXY\_j YntU'g' fY\_] [ , ' \_UnbU ' j ' Ubia ' gU\U'UfibXU'5\_gU'YbYfUH f [ fi Vi ž [ ' j Yb] ] f \_ j Y ] XYU' dYfz:fa Ubq gU ' UF" y fY] Yb' h a ' YbYfUH f [ fi d'Ufi" ] , bž" b' f' b' Yg] j Y ŽUVf \_ U' ja U' UhiYg] j' n' d' r' r'

• ? cbffc`? Uffi

9!G9F -9G'I nU\_HUb? i a UbXU' i? cbffc` DUbY ]

•

! :  
! :  
! :  
! :  
! :  
! :  
! :

! :  
! :  
! :  
! :

HELP DEVICE

! :  
! :  
! :

Motor Modeli		V3300-E2B
	1500 d/dk	33 kW [45HP]
	1800 d/dk	39 kW [53HP]
	2400 d/dk	kW [HP]
	2900 d/dk	kW [HP]
	3000 d/dk	kW [HP]
	3600 d/dk	kW [HP]
	ž	3
	"	0
		0
MJ ? UdUg]hYg]	L	11
Su Kapasitesi	L	14
Yanma Hava Debisi	50Hz (m <sup>3</sup> /dk)	4
	60Hz (m <sup>3</sup> /dk)	4
Gc i İa U'Gi m '5_j '8YV]g]	50Hz (L/dk)	53
	60Hz (L/dk)	44
8Yb]n'Gi m 'Dca dUgi'6Uga U'M_gY_] ]	m	506
MJ_ihH'_Yhja ]	%100 yükte(L/sa-50Hz)	9
	%75 yükte(L/sa-50Hz)	6
	%50 yükte(L/sa-50Hz)	5
	%100 yükte(L/sa-60Hz)	11
	%75 yükte(L/sa-60Hz)	8
	%50 yükte(L/sa-60Hz)	6

Üretici		Onan
		ONAN
	kW	32
Cos Fi		1
		1

Kubota

Onan

CUMMINS ONAN DIGITAL DISPLAY

	fl "L	fl "L			X6 f15 f%a YfY 'tUa m_HYŁ
	590	1358	622	731	69
	fl "L	fl "L			X6 f15 f%a YfY 'tUa m_HYŁ
	590	1358	1358	1358	1358